ELKATO

# سـوئيـچ الكـاتـو




## EL-1SBL082BP-120W



| EL-1SBL082BP-120W | |
|---|---|
| **Technical Specification** | |
| **Layer** | **Layer2** |
| **Managed** | **No** |
| **Switching Capacity** | **2 Gbps Full duplex** |
| **Packet Forwarding Rate** | **0.1488Mpps/port** |
| **MAC Table Size** | **2K** |
| **Network Protocol:** | **IEEE802.3i/802.3u/802.3x/802.3af** |
| **LPP/BSP** | _ |
| **VLAN** | _ |
| **Extend (250M/10Mps)** | _ |
| **AI Watchdog** | _ |
| | |
| | |
| **Hardware Feature** | |
| **Power Supply Type** | **Bult-in** |
| **PoE** | **YES** |
| **Ethernet Port** | **8** |
| **Uplink Port** | **2** |
| **Optical Port** | **0** |
| **Ethernet Port Rate** | **100Mps** |
| **Uplink Port** | **100Mps** |
| **Optical Port Rate** | **N/A** |
| **Power Supply** | **240V AC** |
| **Operating Temperature** | **-10 -50** |
| Operating Humidity | 10%-95% , non-condensing |
| Power Consumption | <5w |
| | |
| PoE | |
| PoE Standard | IEEE802.3af, IEEE802.3at |
| PoE Budget | Max. 30W Output of Single PoE Port |
| | |
| General | |
| ESD | Air discharge: 1.5kV<br>Contact discharge: 1.5kV |
| Thunderproof | Common mode:1.5kV<br>Differential mode: 1.5kV |
| Dimensions(L×W×H): | **170*90*40 mm** |