

ELKATO

سوئیچ الکتو



EL-2SG0822GP



EL-2SG0822GP	
Technical Specification	
Layer	Layer2 Industrial switch
Managed	No
Switching Capacity	24 Gbps Full duplex
Packet Forwarding Rate	1.488Mpps/port
MAC Table Size	8K
Network Protocol:	IEEE802.3i/802.3u/802.3x
LPP/BSP	YES
VLAN	YES
Extend (250M/10Mps)	NO
AI Watchdog	YES
Hardware Feature	
Power Supply Type	Bult-in
PoE	YES
Ethernet Port	8
Uplink Port	2
Optical Port	2
Ethernet Port Rate	1000Mps
Uplink Port	1000Mps
Optical Port Rate	1000Mps
Power Supply	240V AC
Operating Temperature	-40°C-80°C
Operating Humidity	10%-95% , non-condensing
Power Consumption	<5w
PoE Power Budget:	120W - 52V
PoE	
PoE Standard	IEEE802.3af, IEEE802.3at
PoE Budget	8*10/100/1000M POE ports
installation	High strength iron shell, DIN35 Rail installation
General	
ESD	Air discharge: 6kV Contact discharge: 6kV
Thunderproof	Common mode:6KV Differential mode: 6KV
Dimensions(L×W×H):	153*128*49mm