

ELKATO

سوئیچ الکتو



EL-1SB2422GP-320W(V2)



EL-1SB2422GP-320W(V2)	
Technical Specification	
Layer	Layer2
Managed	No
Switching Capacity	8.8 Gbps Full duplex
Packet Forwarding Rate	0.1488Mpps/port
MAC Table Size	2K
Network Protocol:	IEEE802.3i/802.3u/802.3x/802.3af/802.3at
LPP/BSP	NO
VLAN	YES
Extend (250M/10Mps)	YES
AI Watchdog	YES
Hardware Feature	
Power Supply Type	Bult-in
PoE	YES
Ethernet Port	24
Uplink Port	2
Optical Port	2
Ethernet Port Rate	1000Mps
Uplink Port	1000Mps
Optical Port Rate	1000Mps
Power Supply	240V AC
Operating Temperature	-10°C-50°C
Operating Humidity	10%-95% , non-condensing
Power Consumption	<5w
PoE Power Budget:	320W
PoE	
PoE Standard	IEEE802.3af, IEEE802.3at
PoE Budget	Port 1–24≤30W//Max. 30W Output of Single PoE Port
General	
ESD	Air discharge: 1.5kV Contact discharge: 1.5kV
Thunderproof	Common mode:4kV Differential mode: 1.5kV
Dimensions(L×W×H):	440*195*45mm (L*W*H)